

IW-RS104-02SN

1U Storage Rackmount Server Chassis



Features & Benefits

- External 3.5" x 4 or 2.5" x 4 hot-swap HDD trays with lock supported
- Internal 2.5" x 2 HDD Support
- Easy-swap 4028 mm PWM fans with Anti-Vibration mechanism
- Built in Info-Tag for systems easy management
- Supports 6Gb/s SATA/SAS or 12Gb/s Mini-SAS HD backplane



Specifications

| | |
|---|--|
| Standard | EIA-RS310D |
| M/B Form Factor | ATX (12" x 10") |
| Dimensions (D x W x H) w/o Front Panel | 533.4 x 482.6 x 44.4 mm (21" x 19" x 1.75") |
| Drive Bay | External: Slim ODD x 1 or 2.5" x 1 (Optional), Hot-Swap 3.5" x 4 or 2.5" x 4 Internal: 2.5" x 2 |
| Power Supply | Supports <ul style="list-style-type: none">▪ Form Factor: Flex, 1U single, 1U 1+1 Redundant PSU▪ Watt: Flex up to 400W, Single 500W, Redundant up to 300W |
| Indicator | Power Status, HDD, LANs, System Fail Activity LEDs |
| Front Control Panel | Power Switch, ID Switch, System Reset, NMI, USB 3.0 x 2 |
| Backplane | <ul style="list-style-type: none">▪ SATA x 4 (6Gb/s Supported)▪ Mini SAS HD (12Gb/s Supported) |
| Cooling Fan | Supports 40 x 28 mm PWM Easy-Swap Fan x 6 |
| Expansion Slot | Full Height PCI Slot x 1 (via riser card and bracket) |
| Material | Material: SGCC Thickness: 1.0 mm |
| Rail Kit | Supports 28" Ball-bearing slide rail |
| Packaging Dimensions (D x W x H) | 700 x 570 x 180 mm |
| Shipping Information | Net Weight: 5.63 kg Gross Weight: 9.11 kg Container Info <ul style="list-style-type: none">▪ Single Packing with pallets: 20': 384pcs, 40': 800pcs, 40'H: 900pcs |

* The actual product is subject to change without prior notice. In Win Development Inc. reserves the right to make final modifications.

* Above image for reference only. All hardware components are not included.



CONTEMPORARY & INNOVATIVE
www.in-win.com